

Specification for Green Rescue Laser Flare (GLF)													
Model	GLF – Green Rescue Laser Flare												
Wavelength	532nm												
Classification	CW, <5mW, Class IIIa final output power												
Power Supply	One 3V CR123 Lithium Battery Approximate 5 operating hours per battery												
Beam Shape	3 deg. divergent laser line												
NOHD Nominal Ocular Hazard Distance	1mW output at 9', beam width 0.78"												
Operating Temp.	Typical 15° C ~ 45° C												
Laser Operation	Twist cap laser activation												
Construction	Anodized 6061-T6 aluminum, waterproof to 80 feet (24m)												
Dimensions	4.72"(L) x 0.88"(dia.)												
Weight	2.75 oz. without battery												
Dimension Drawing													
Product Label	<div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center;">It is illegal to point this device at an aircraft except in an emergency!</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p style="text-align: center;">LASER RADIATION AVOID DIRECT EYE EXPOSURE CLASS 3R LASER PRODUCTS 530-680nm, 5mW cw max.</p> <p style="text-align: center;">Complies with: IEC/EN 60825-1, 2007-03 US DHHS 21 CFR Subchapter J</p> </div> <div style="width: 45%; text-align: right;"> <p>↑↑ LASER APERTURE ↑↑</p> <p>Greatland Laser Rancho Cucamonga, CA, USA Model: Green Rescue Laser Flare® Manufactured: 2013 2014 2015</p> <table style="width: 100%; text-align: center;"> <tr> <td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td> </tr> <tr> <td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><td>12</td> </tr> </table> <p style="font-size: 2em; font-weight: bold;">H00001</p> </div> </div> <p style="text-align: center; font-weight: bold;">Serial Number: GLF032-01</p> </div>	1	2	3	4	5	6	7	8	9	10	11	12
1	2	3	4	5	6								
7	8	9	10	11	12								