

Oil Change System: GP-800 Series

Fast lube oil change system drains used oil and fills new oil to multiple equipment.

Basic Features

- Self-priming
- Motor equipped with thermal protection
- Cable for electrical connection
- Drain and fill switch
- Valve options 3-7
- Available in 110V



Technical Specifications

Flow Rate	3 GPM / 12 LPM	
Voltage	110V 60Hz	
Pump Port	3/8" Male NPT	
Manifold Port	1/2" Female NPT	
Max. Amp. Draw	4A	
RPM	2800	
Gears	Bronze	
Shaft	Stainless steel	
Self-Priming	5 ft / 1.5 m (wet gears)	
Max. Lift	15 ft / 5 m with foot valve	
Dimensions	A	12.75" / 324 mm
GP-803 (3 Valve)	B	12.75" / 324 mm
	C	6.3" / 160 mm
	A	12.75" / 324 mm
GP-804 (4 Valve)	B	12.75" / 324 mm
	C	6.3" / 160 mm
	A	16.25" / 413 mm
GP-805 (5 Valve)	B	12.75" / 324 mm
	C	6.3" / 160 mm
	A	16.25" / 413 mm
GP-806 (6 Valve)	B	12.75" / 324 mm
	C	6.3" / 160 mm
	A	19.5" / 495 mm
GP-807 (7 Valve)	B	12.75" / 324 mm
	C	6.3" / 160 mm



Reversing switch

