

KK3-8.5 KW

KEEL COOLED / DRY EXHAUST

MODEL		KK3-8.5 KW
ENGINE	KUBOTA	D1105-E3BG
CYLINDERS		THREE (3)
CUBIC INCH		68.53
BORE & STROKE		3.07 x 3.09
H.P. @ 1800 RPM		15.4
ASPIRATION		NATURAL
COOLING SYSTEM		KEEL COOLED / HOT MANIFOLD
EXHAUST	2.0"	DRY EXHAUST FLANGE
FUEL INLET		5/16
FUEL RETURN		3/16
DIMENSIONS		L 34.0 x W 22.0 x H 29.0
WEIGHT		550 LBS
MODEL		STAMFORD/NEWAGE
OUTPUT VOLTS		120 / 240 / SINGLE PHASE
OUTPUT AMPS		70.83 x 35.42
OUTPUT WATTS		8,500

STANDARD FEATURES

12 VOLT DC START / CHARGING
AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE
FUEL FILTER
FUEL TRANSFER PUMP
AIR INTAKE SILENCER / CLEANER
FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL MOUNTING FRAME
SINGLE BEARING GENERATOR
BRUSHLESS EXCITOR
START / STOP / PREHEAT / HOURMETER (*mounted on machine*)

OPTIONAL EQUIPMENT

REMOTE START / STOP PANEL W / 20FT EXTENSION HARNESS
DC GAUGE PANEL W / START / STOP / 20FT EXTENSION HARNESS
THREE PHASE ELECTRICAL END
CIRCUIT BREAKER
ELECTRIC FUEL PUMP
WET EXHAUST MANIFOLD (*mounted on engine*)