KK3-7.0 KW

KEEL COOLED / DRY EXHAUST

MODEL KK3-7.0 KW

ENGINE KUBOTA D1005-E3BG
CYLINDERS THREE (3)
CUBIC INCH 61.08
BORE & STROKE 2.99 x 2.90

H.P. @ 1800 RPM 13.1
ASPIRATION NATURAL

COOLING SYSTEM KEEL COOLED / HOT MANIFOLD

EXHAUST 2.0" DRY EXHAUST FLANGE

FUEL INLET5/16FUEL RETURN3/16

DIMENSIONS L 35.0 x W 24 x H 29.0"

WEIGHT 520 LBS

MODEL STAMFORD/NEWAGE
OUTPUT VOLTS 120 / 240 / SINGLE PHASE

OUTPUT AMPS 58.33 x 29.17

OUTPUT WATTS 7,000

STANDARD FEATURES

12 VOLT DC START / CHARGING

AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE

FUEL FILTER

FUEL TRANSFER PUMP

AIR INTAKE SILENCER / CLEANER

FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL MOUNTING FRAME

SINGLE BEARING GENERATOR

BRUSHLESS EXCITOR

START / STOP / PREHEAT / HOURMETER (mounted on machine)

OPTIONAL EQUIPMENT

REMOTE START / STOP PANEL W / 20FT EXTENSION HARNESS
DC GAUGE PANEL WITH START / STOP / 20FT EXTENSION HARNESS

THREE PHASE ELECTRICAL END

CIRCUIT BREAKER
ELECTRIC FUEL PUMP

WET EXHAUST MANIFOLD (mounted on engine)