

KK4-12.5 KW

KEEL COOLED / DRY EXHAUST

MODEL		KK4-12.5 KW
ENGINE	KUBOTA	V1505-E3BG
CYLINDERS		FOUR (4)
CUBIC INCH		91.41
BORE & STROKE		3.07 x 3.09
H.P. @ 1800 RPM		20.2
ASPIRATION		NATURAL
COOLING SYSTEM		KEEL COOLED / HOT MANIFOLD
EXHAUST	2.0"	DRY EXHAUST FLANGE
FUEL INLET		5/16
FUEL RETURN		3/16
DIMENSIONS		L 35.0 x W 24.0 x H 29.0
WEIGHT		600LBS
MODEL		STAMFORD/NEWAGE
OUTPUT VOLTS		120 / 240 / SINGLE PHASE
OUTPUT AMPS		104 / 52
OUTPUT WATTS		12,500

STANDARD FEATURES

12 VOLT DC START / CHARGING
AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE
FUEL FILTER
FUEL TRANSFER PUMP
AIR INTAKE SILENCER / CLEANER
FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL MOUNTING FRAME
SINGLE BEARING GENERATOR
BRUSHLESS EXCITOR
START / STOP / PREHEAT / HOURMETER (*mounted on machine*)

OPTIONAL EQUIPMENT

REMOTE START / STOP PANEL W / 20FT EXTENSION HARNESS
DC GAUGE PANEL WITH START / STOP / 20FT EXTENSION HARNESS
THREE PHASE ELECTRICAL END
CIRCUIT BREAKER
ELECTRIC FUEL PUMP
WET EXHAUST MANIFOLD (*mounted on engine*)