

KK4-30.0 KW

KEEL COOLED / DRY EXHAUST

MODEL	MARINE CERTIFIED	KK4-30.0 KW
ENGINE'	KUBOTA	V3300-E3BG
CYLINDERS		FOUR (4)
CUBIC INCH		202.48
BORE & STROKE		3.86 x 4.33
H.P. @ 1800 RPM		45.1
ASPIRATION		NATURAL
COOLING SYSTEM		KEEL COOLED / HOT MANIFOLD
EXHAUST	3.0"	DRY EXHAUST FLANGE
FUEL INLET		5/16
FUEL RETURN		3/16
DIMENSIONS		L 55.0 x W 30.0 x H 38.0
WEIGHT		1300Lbs
MODEL		STAMFORD/NEWAGE
OUTPUT VOLTS		208 VOLTS / THREE PHASE
OUTPUT AMPS		83.3
OUTPUT WATTS		30,000

STANDARD FEATURES

12 VOLT DC START / CHARGING
AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE
FUEL FILTER
FUEL TRANSFER PUMP
AIR INTAKE SILENCER / CLEANER
FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL MOUNTING FRAME
SINGLE BEARING GENERATOR
BRUSHLESS EXCITOR
START / STOP / PREHEAT / HOURMETER (mounted on engine)

OPTIONAL EQUIPMENT

REMOTE START / STOP PANEL W / 20FT EXTENSION HARNESS
DC GAUGE PANEL WITH START / STOP / 20FT EXTENSION HARNESS
SINGLE PHASE ELECTRICAL END
CIRCUIT BREAKER
ELECTRIC FUEL PUMP
WET EXHAUST MANIFOLD (mounted on engine)