


# K3-11.5KW

## (50 Hertz)

### Standard Features

- Kubota Diesel Engine
- Single bearing direct coupled brushless generator
- +/- 1% Solid-state voltage regulation
- Low 1,500 RPM operating speed
- Safety shutdown system for high coolant temperature or low lube oil pressure
- Tinned wiring
- Freshwater double pass heat exchanger
- Water-cooled exhaust manifold with removable intergral Cupro-Nickel heat exchanger core
- Zinc anode in heat exchanger
- Stainless Steel exhaust elbow cast
- Gear-driven raw water pump
- 4-Point isolation mounts S/S
- Molded blue silicone water hoses with Stainless Steel AWAB clamps
- Air intake Cleaner / Silencer
- Spin-on lube filter
- Secondary 5 Micron fuel filter
- Self-bleed fuel system
- USCG approved fuel lines
- Electric fuel transfer pump
- Forged brass oil drain valve with safety lock
- Awl-Craft 2000 urethane finish
- Circuit breaker - main line
- Belt guard
- 5-Year Limited Warranty



### Specifications

Kubota Model	D1503-M-E4BG
Cylinders	3
Cu. In. Displacement	91.47
Bore x Stroke	3.27 x 3.64 (in.)
Dims (LxWxH)	34.5 x 21 x 26 (in.)
Enclosure Dims (LxWxH)	37.5 x 24 x 28 (in.)
Weight (lbs.)	649
Output (volts)	230
Output (amps)	50
Output (watts)	11,500
Exhaust Dia.	2 in.
Raw water Dia.	1 in.
Fuel Line Dia.	5/16 in.
Return Line Dia.	3/16 in.

*Specifications are subject to change without notice*

### Optional Equipment

- Remote Start / Stop - 20ft. Harness
- DC Gauge Panel - 20ft. Harness
- Stainless Steel Drip Pan
- Three Phase Generator Output
- 24-Volt Starting System
- Sound Insulation Blanket
- Powder Coated Aluminum Enclosure
- Spare Parts Kit



2880 Hammondville Road • Pompano Beach, FL 33069  
Ph: 954-979-5899 • Fax: 954-979-4349  
info@phasormarine.com • www.phasormarine.com

rev112323